Portec Belt Curve Inquiry Form

Customer # Quote # Date:	
Name:	Salesperson:
Company:	Project Time Frame:
Department:	□1-2 mos □2-6 mos □6-12 mos
Project:	□ Unknown □ Budget
Address:	Decision Time Frame:
Phone: Fax:	□ 1-3 wks □1-2 mos □2-6 mos
Product Information	□6-12 mos □ Unknown
Material Handled:	Application Information
	Distance between packages: mm
	Is product transfer a concern? □ Yes □ No
Product Dimensions	Is product orientation critical? □ Yes □ No
Length: mm	If yes, explain:
Width: mm	Are there any special environmental conditions,
Height: mm	oil, chemicals, moisture, etc.? □ Yes i.e., dust, □ No
Product Weight: kg	If yes, specify:
Design Load (if applicable): kg/m	
	Ambient Temperature: °C
□ Packaged I □ Not Packaged	Clean Room Freezer
Is there anything special about the product? □ Yes □ No	□ Bakery Application □ Raw Meat Application
If yes, specify:	Oils used in product:
	Accessories
Surface Contact belt, i.e., (product on shrink-wrap, plastic tote,	Drive package required? □ Yes □ No
cardboard, furniture with feet, etc.):	Customer Supplied Drives: Refer to factory.
Will Portec Curves be placed into an “S” configuration? □ Yes □ No	Customer supplied drives to: □ Portec □ Site
	Motor Brand: □ SEW
Technical Information	Gear Reducer Brand: □ SEW
Equip. Spec: Revision #:	Motor voltage required: V. Ph. Hz.
Model Number (if known):	
Degrees of arc:	Sideguard height at inside radius: mm
Direction of travel: Drive location:	Sideguard height at outside radius: mm
Belt speed required at centerline:	Supports required? □ Yes □ No
Reversible operation? □ Yes □ No How often?	If yes, required top of bed height: mm
Duty cycle: Hours per day:	Ceiling hanger brackets required? □ Yes □ No
Start/Stop cycle: Cycles per minute	Underguarding? □ None □ Plastic mesh
Nominal conveying width: mm	□ Solid under-pan □ Expanded metal
(between sideguard dimension)	Quick removal thumbscrews? □ Yes □ No
(Exposed belt width is 12mm narrower than conveying width)	
Belt material required:	Shipping & Receiving
Belt Splice: □ laced □ vulcanized endless	Does customer have receiving limitations? □ Yes □ No
Frame Construction:	(i.e., doorway, ceiling, aisle) □ Yes □ No
	If yes, define:
□ Stainless Steel □ Mild steel	
Paint color required:	
Paint type required: □ Std. Quick-dry enamel	Special truck and shipping instructions:
□ Other (specify):	
(Refer to Portec paint policy)	
Comments	